

FITZPATRICK, CELLA, HARPER & SCINTO

30 Rockefeller Plaza
New York, NY 10112-3801
(212) 218-2100

Facsimile:(212) 218-2200

FACSIMILE COVER SHEET

TO:	Examiner A. Tugbang U.S. Patent and Trademark Office	
FROM:	Douglas W. Pinsky	
RE:	Application No.: 09/339,869 Attorney Dkt. No.: 03500.013613	
FAX NO.:	(703) 746-4258	
DATE:	September 23, 2004	NO. OF PAGES: 4 (including cover page)
TIME:	SENT BY: tina	

MESSAGE

Per our telephone conversation

**IF YOU DO NOT RECEIVE ALL THE PAGES
PLEASE CALL 202-530-1010 AS SOON AS POSSIBLE.**

Note: We are transmitting from a Canon Model FAX-L770
(compatible with any Group I, Group II or Group III machine).

THIS FACSIMILE MESSAGE AND ACCOMPANYING DOCUMENTS ARE INTENDED ONLY FOR THE USE OF THE ADDRESSEE INDICATED ABOVE. INFORMATION THAT IS PRIVILEGED OR OTHERWISE CONFIDENTIAL MAY BE CONTAINED THEREIN. IF YOU ARE NOT THE INTENDED RECIPIENT, YOU ARE HEREBY NOTIFIED THAT ANY DISSEMINATION, REVIEW OR USE OF THIS MESSAGE, DOCUMENTS OR INFORMATION CONTAINED THEREIN IS STRICTLY PROHIBITED. IF YOU HAVE RECEIVED THIS MESSAGE IN ERROR, PLEASE NOTIFY US IMMEDIATELY BY TELEPHONE OR FACSIMILE AND MAIL THE ORIGINAL TO US AT THE ABOVE ADDRESS. THANK YOU.

Application NO. 09/339,869
Attorney Docket No. 03500.013613

1. (Currently Amended) A method for processing an ink discharge port of an ink jet head provided with discharge ports for discharging ink, the discharge ports being provided at respective discharge port positions on a discharge port plate, the method comprising the steps of:

closely contacting a mask plate having openings corresponding to the discharge ports with a face of the discharge port plate on an ink discharge side; and

forming the discharge port on the discharge port plate by irradiating plural high energy ultraviolet beams simultaneously through the mask plate so that the beams are inclined with respect to a vertical axis that is perpendicular to the mask plate,

wherein the plural beams are simultaneously irradiated at one of the respective discharge port positions of the discharge port plate to form the discharge port and are incident at the single discharge port position from different directions, and

wherein the formed discharge port has ~~a shape that widens~~ an area that increases in a direction away from a source of the beams.

6. (Currently Amended) A method for manufacturing an ink jet head provided with discharge ports for discharging ink and a discharge port plate having the discharge ports at respective discharge port positions, the method comprising the steps of:

closely contacting a mask plate having openings corresponding to the discharge ports with a face of the discharge port plate on an ink discharge side; and

Application NO. 09/339,869
Attorney Docket No. 03500.013613

forming a discharge port on the discharge port plate by irradiating plural high energy ultraviolet beams simultaneously through the mask plate so that the beams are inclined with respect to a vertical axis that is perpendicular to the mask plate,

wherein the plural beams are simultaneously irradiated at one of the respective discharge port positions of the discharge port plate to form the discharge port and are incident at the single discharge port position from different directions, and

wherein the formed discharge port has ~~a shape that widens~~ an area that increases in a direction away from a source of the beams.

32. (Currently Amended) A method for processing an ink discharge port of an ink jet head provided with discharge ports for discharging ink, the discharge ports being provided at respective discharge port positions on a discharge port plate, the method comprising the steps of:

closely contacting a mask plate having openings corresponding to the discharge ports with a face of the discharge port plate on an ink discharge side; and

forming the discharge port on the discharge port plate by irradiating plural high energy beams simultaneously through the mask plate so that the beams are inclined with respect to a vertical axis that is perpendicular to the mask plate,

wherein the plural beams are simultaneously irradiated at a single discharge port position of the discharge port plate to form the discharge port and are incident at the single

Application NO. 09/339,869
Attorney Docket No. 03500.013613

discharge port position from different directions, and

wherein, ~~after the formation of the discharge port,~~ the formed discharge port has a ~~shape that widens~~ an area that increases in a direction away from a source of the beams.

DC_MAIN 178912v1